

# TOOL FEATURES

- Easy to handle thanks to it's light weight and good balance
- Includes switchable trigger for full sequential fire and bump fire
- Tool-free depth of drive adjustment

# 0° PLASTIC SHEET COIL NAILS

Also available with BECK DIAMOND COATING

- Drastically increased holding power: + 20 % and more
- Reduced drive-in resistance: up to 10 %
- Significantly longer installation tool service life - protects tool components



## **CONTACT & SERVICE**

Our sales team is available at:

P +1 800 239 8665 sales@beck-america.com www.beck-america.com

## **DESCRIPTION**

- Drives 0° plastic sheet coil nails
- · Fully pneumatic feeding and positioning system allows precise nailing
- Rubber comfort grip and adjustable exhaust
- Belt hook
- Removable no mar tip



#### **BECK AMERICA**

105 Industrial Park Drive 35661 Muscle Shoals, Alabama | USA P +1 800 239 8665 | F +1 256 381 6659 E sales@beck-america.com | W www.beck-america.com







## **F44AC CN0-PS65**

#### **APPLICATIONS**

- Siding
- Fencing
- Sub-flooring
- Decking
- Roof joists
- · Garden furniture
- · Boxes and crates

## **HANDLING**

- 1. Load the coil in the magazine
- 2. Position first nail in nose channel and align top of nails with upper edge loading channel
- 3. Connect air supply
- 4. Avoid a dry or dirty tool by lubricating respectively cleaning regularly

## **TOOL CHARACTERISTICS**

Height	Width
331 mm	145 mm
13.03 inch	5.71 inch
Length	Weight
Lengui	weight
281 mm	2.25 kg

#### **Pressure**

5 - 8 bar | 70 - 120 psi

### Air consumption per shot

1.20 L. | 0.042 SCF Performance at 90 psi | 6.2 bar (0.62 MPa)

## **FASTENER DATA**

Diameter	2.20 - 2.50 mm   0.087 - 0.098"
Shank	smooth   ring   screw   knurled
Head	5.8 mm   0.228"
Pitch	6.35 mm   0.25"
Length	32 - 63 mm   1 ½ - 2 ½"
Capacity	325 nails
Nail Type	0° Plastic Sheet Coil Nails (CN)

## **NOISE VALUE**

 $\begin{array}{l} \text{(EN 12549+A1: 2008, EN ISO 4871: 2009)} \\ L_{\text{WA,1s}}: 92.02 \text{ dB (A)} - K_{\text{WA,1s}} \text{, } 2.5 \\ L_{\text{pA,1s}}: 81.50 \text{ dB (A)} - K_{\text{pA,1s}} \text{, } 2.5 \end{array}$ 

#### **VIBRATION VALUE**

(UNI ISO/TS 8662-11)  $3.47 \text{ m/s}^2$ 

#### **ACTUATION & LOADING**

Actuation System: Single shot & contact actuation

Loading: Coil

#### **BENEFITS:**

## 0° PLASTIC SHEET COLLATION

- · Extremely flexible
- Reduced jamming, thanks to the straight nail feed of the plastic sheet collation
- Clear advantages of plastic sheet collation compared to wire collation: superior feeding, no wire flagging and thus a smoother surface, no debris flying around
- The plastic sheet can be recycled

