



TRIMFAST[®] HEAVY DUTY MODEL 210

DESCRIPTION

- Engineered for the power and durability required for use with light gauge steel
- Accepts T-Nail style hardened trim pins
- Power to fasten to 14 ga steel at the speed of nailing to wood
- Operates using typical jobsite air compressor at 120 psi maximum
- Capable of driving pins 1 1/2" to 2-1/2" long
- Systems approach with tools and fasteners provides single source responsibility
- Comes standard with plastic carrying case



CONTACT & SERVICE

Our sales team
is available at:

T +43 7724 2111-671
sales.int@beck-fastening.com
www.beck-fastening.com

PIN TYPE

AST-100 TRIMFAST[®] HEAVY DUTY TRIM PINS

TRIMFAST® HEAVY DUTY MODEL 210

TOOL CHARACTERISTICS

Height	Width	Length	Weight
12 inch	3 1/2 inch	11 1/2 inch	6 lbs
305 mm	89 mm	292 mm	2.72 kg

Pressure 85 - 120 psi | 6 - 8 bar

Lubricant Non-detergent pneumatic tool lubricant

Recommended steel thickness

20 ga - 14 ga



Model 210

FASTENER DATA

Pin Type	AST-100-0150G	AST-100-0200G	AST-100-0250G
Wire	0.086" 2.20 mm		
Shank	Smooth		
Head	1/4" 6 mm		
Length	1 1/2" 39 mm	2" 50 mm	2 1/2" 63 mm
Coating	Electro Galvanized		
Magazine Capacity	50 pins		

ACTUATION & LOADING

Actuation System:

Single sequential actuation

Loading:

Magazine with latch

APPLICATIONS

- James Hardie® XLD fiber cement trim to light gauge steel framing
- Miratec® treated exterior composite trim to light gauge steel framing
- Wood furring and exterior trim to light gauge steel framing
- Wood or metal furring to CMU